Ensure that Input Is Properly Canonicalized

William L. Fithen, Software Engineering Institute [vita³]

Copyright © 2005 Carnegie Mellon University

2005-10-03

Failure to canonicalize input can introduce vulnerability. Inadvertently canonicalizing input multiple times can introduce vulnerability.

Description

Canonicalization is the process of transforming a potentially flexible data structure into one that has guaranteed characteristics. It is a frequent technique for input data validation. For example, the same input data "characters" can be encoded in many ways, ranging from 7-bit ASCII to variable-width multibyte Unicode. Before a program that accepts such input uses it, it is frequently required that the input be transformed into some canonical form that is universal (in the context of the program). Otherwise, even simple text comparisons (e.g., length, equal, ordering) cannot be made.

For extensive coverage of this issue see [Howard 02⁴ Chapter 10: All Input Is Evil!⁵].

Failure to Canonicalize (When It Was Needed)

When input with identical semantics can be supplied in multiple syntaxes, then it is usually wise to define one of the syntaxes as "canonical" and transform all of the other representations into that one before using the input. Even better is to disallow all input that is not canonical [Hoglund 04⁶].⁷

Redundant Canonicalization (Which Is Not Idempotent)

When canonicalization of input is required, be sure that it only occurs once. In many representations, it is not safe to canonicalize already canonicalized input [VU#5802999].

References

[Hoglund 04] Hoglund, Greg & McGraw, Gary. Exploiting Software: How to Break Code. Boston, MA: Addison-Wesley. 2004.

- 3. daisy:320 (Fithen, William L.)
- 4. #Howard-02
- 5. http://www.microsoft.com/mspress/books/sampchap/5957.asp#SampleChapter
- 6. https://buildsecurityin.preview.us-cert.gov/daisy/bsi/articles/knowledge/guidelines/331/edit/39405b5e8457707b4d313e3d382d1e80687330
- 7. This can sometime be difficult when the input data is some other system's input or output and that system defines multiple representations as being legal. Examples include: DNS hostnames, IP addresses, path names in filesystems, and even numerical values.
- 8. It is possible to define canonical forms that can be redundantly canonicalized without damage. For example, removing leading zeroes from integer values or removing "../" and "./" sequences from filesystem path names can be performed multiple times without harm.
- 9. #VU-580299

[Howard 02] Howard, Michael & LeBlanc, David. Writing Secure Code. 2nd. Redmond,

WA: Microsoft Press, 2002.

[VU#580299] MacInnis, Ken. Vulnerability Note VU#580299: Microsoft Internet Explorer

contains URL decoding cross-domain vulnerability. June 14, 2005.

http://www.kb.cert.org/vuls/id/580299.

SEI Copyright

Carnegie Mellon University SEI-authored documents are sponsored by the U.S. Department of Defense under Contract FA8721-05-C-0003. Carnegie Mellon University retains copyrights in all material produced under this contract. The U.S. Government retains a non-exclusive, royalty-free license to publish or reproduce these documents, or allow others to do so, for U.S. Government purposes only pursuant to the copyright license under the contract clause at 252.227-7013.

Permission to reproduce this document and to prepare derivative works from this document for internal use is granted, provided the copyright and "No Warranty" statements are included with all reproductions and derivative works.

For inquiries regarding reproducing this document or preparing derivative works of this document for external and commercial use, including information about "Fair Use," see the Permissions¹ page on the SEI web site. If you do not find the copyright information you need on this web site, please consult your legal counsel for advice.

Velden

Naam	Waarde
Copyright Holder	SEI

Velden

Naam	Waarde
is-content-area-overview	false
Content Areas	Knowledge/Guidelines
SDLC Relevance	Implementation
Workflow State	Publishable

^{1.} http://www.sei.cmu.edu/about/legal-permissions.html